

CLAIMS

1. A particulate filter for an internal combustion engine comprising:

- a microwave source generating microwaves;
- microwave-absorbing materials to absorb said microwaves and
- 5 generate heat; and
- a particulate trap trapping particulates generated by the engine, said particulate trap heated by said microwave-absorbing materials to burn off said particulates.

2. The particulate filter of Claim 1 wherein said microwave-absorbing material is configured as an end plug.

3. The particulate filter of Claim 1 wherein said microwave-absorbing material is configured as axial bands distributed along channels of said particulate trap.

4. The particulate filter of Claim 1 wherein said microwave-absorbing material is deposited in substantially linear fashion along the length of the channels of said particulate trap.

5. The particulate filter of Claim 1 wherein said microwave-absorbing material is silicon carbide.

6. The particulate filter of Claim 1 wherein said particulate trap is comprised of a microwave-transparent material.

7. The particulate filter of Claim 6 wherein said microwave-transparent material is chordierite.

4009666-1-1-94
105111-555000F

8. A method of regenerating a particulate trap comprising:
 generating microwave radiation; and
 absorbing microwaves to generate heat to burn particulates in the
 particulate trap.

9. The method of Claim 8 further comprising the step of
 depositing microwave-absorbent material along walls of the particulate trap.

10. The method of Claim 8 further comprising the step of
 configuring microwave-absorbent material as end plugs in the particulate
 trap.

11. The method of Claim 8 further comprising the step of
 controlling the temperature of the particulate trap by controlling the
 microwave radiation.

12. A system for removing particulates in a particulate trap
 comprising:

- a microwave power source;
- a microwave antenna coupled to said power source for generating
 5 microwaves;
- a microwave wave guide operatively coupled to said microwave
 antenna to guide said microwaves; and
- microwave-absorbent material located in said particulate trap,
 wherein said microwaves are incident upon said microwave-absorbent
 10 material to generate heat to burn off particulates located in said particulate
 trap.

13. The system of Claim 12 further comprising a diesel engine coupled to said particulate trap, wherein diesel exhaust propagates through said particulate trap.

14. A method of initiating regeneration in a particulate trap comprising the steps of:

locating microwave-absorbing material in the particulate trap in areas that particulates build up;

5 generating microwaves;

absorbing microwaves with the microwave-absorbing material;

and

controlling the microwaves to initiate a burn-off of particulates.

10003688 111594